


HOIST ANCHOR BASE

316 STAINLESS STEEL



| ITEM | SIZE | A | B | C | D | E | F | WLL | WT |
|------------|-----------|-------|-------|-------|-------|--------------|-------|--------|------|
| | (nominal) | | | | | (UNC thread) | | (lb) | (lb) |
| S0116-HB07 | 1/4" | 0.31" | 1.38" | 1.00" | 0.75" | 3/8"- 16 | 0.45" | 1,000 | 0.12 |
| S0116-HB08 | 5/16" | 0.38" | 1.63" | 1.20" | 0.88" | 7/16"- 14 | 0.48" | 1,300 | 0.18 |
| S0116-HB10 | 3/8" | 0.44" | 2.00" | 1.50" | 1.25" | 1/2"- 13 | 0.60" | 1,500 | 0.46 |
| S0116-HB12 | 7/16" | 0.50" | 2.13" | 1.56" | 1.38" | 5/8"- 11 | 0.65" | 2,000 | 0.56 |
| S0116-HB13 | 1/2" | 0.63" | 2.25" | 1.59" | 1.38" | 3/4"- 10 | 0.78" | 3,000 | 0.58 |
| S0116-HB16 | 5/8" | 0.75" | 2.67" | 1.86" | 1.75" | 7/8"- 9 | 1.01" | 4,000 | 1.11 |
| S0116-HB20 | 3/4" | 0.88" | 2.89" | 2.00" | 2.00" | 1"- 8 | 1.19" | 6,000 | 1.54 |
| S0116-HB22 | 7/8" | 1.00" | 3.50" | 2.34" | 2.50" | 1-1/8"- 7 | 1.39" | 8,000 | 3.00 |
| S0116-HB25 | 1" | 1.13" | 4.00" | 2.67" | 2.75" | 1-1/4"- 7 | 1.60" | 10,000 | 4.23 |

NOTE:

**316 STAINLESS STEEL FOR MAXIMUM CORROSION RESISTANCE.
DESIGNED FOR USE WITH STANDARD SHACKLE TYPES AND SIZES.**